



FEATURES

- 3-CCT changeable.
- Compatible with leading and trailing edge phase cut dimmers.
- 3-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC85V/270mA
Power	30W
Rated Input Current	0.14A
PF value	>0.9
Ingress Protection	IP54
Operating Temperature	-10-40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Bridgelux LED
CRI	Ra > 80, Ra > 90
Colour temperature	3000K-4000K-5000K
System luminous efficacy up to	85lm/W

Packaging

Box Dimensions	L420 x W100 x H420mm
Box Net Weight	0.803Kg
Box Gross Weight	1.119Kg
Carton Dimensions	L525 x W440 x H445 mm/5 PCS
Carton Net Weight	4.015Kg
Carton Gross Weight	6.40Kg



Model	CCT	Beam Angle		Lumen	Efficacy		Lumen	Efficacy
AC1014-LED-30W	3000K	120°	CRI	1797lm	67lm/W	CRI	1620lm	60lm/W
AC1014-LED-30W	4000K	120°		2123lm	85lm/W		2016lm	80lm/W
AC1014-LED-30W	5000K	120°	80+	1971lm	73lm/W	90+	1773lm	66lm/W