

## BOLT-SLIM-120

### Slim 1200mm LED Batten



#### Description

The BOLT-SLIM LED Batten Series is an ideal modern replacement for traditional T8 and T5 fluorescent battens. Featuring a "quick fix" design, which ensures a hassle-free installation process. This batten comes with a quad wattage option, allowing users to toggle between 20W (600mm) and 40W (1200mm) settings to adjust brightness according to desired light level required. The switch for this adjustment is conveniently located on the LED driver.

Constructed from high-quality pressed sheet metal and finished with a white powder coat, complimented with a high transparency opal polycarbonate diffuser. The BOLT-SLIM Series is available in both 1200mm and 600mm lengths, making it versatile for various settings. Tricolour switchable, allowing the colour temperature output of the LED batten to be changed with a dip switch on the internal driver located inside the fitting. LED Colour temperatures - Warm White 3000K/Neutral White 4000K/White 5700K. Non-dimmable. Suitable for domestic applications such as laundries, garages, and storerooms, as well as commercial environments like underground car parks.



#### Specification Features

Input Voltage:	240V AC
Power (W):	20W/25W/35W/40W
IP rating (IP):	IP44
Lumens (lm):	(20W) Warm White 3000K - 2870lm (25W) Warm White 3000K - 3580lm (35W) Warm White 3000K - 4725lm (40W) Warm White 3000K - 5445lm (20W) Neutral White 4000K - 3020lm (25W) Neutral White 4000K - 3830lm (35W) Neutral White 4000K - 5130lm (40W) Neutral White 4000K - 5830lm (20W) White 5700K - 3015lm (25W) White 5700K - 3795lm (35W) White 5700K - 5005lm (40W) White 5700K - 5625lm
LED type:	SMD
CCT:	3000K - 4000K - 5700K
CRI:	≥80
Beam angle (°):	120°
Dimmable:	No
Lifespan (hrs):	50,000hrs
Installation:	Surface Mounted or Suspended



#### Diagrams / Additional

Item No.	Variant	CCT
<b>BOLT-SLIM-120</b>	66140	TRIO

1200mm

