

BI-PIN HALOGEN GLOBES

- Input voltage: 12V
- 30% energy saving
- Specially suitable for chandeliers and small fittings
- Can be used indoors and outdoors in a waterproof fitting
- Suitable for dimming

2,000
HRS

1 YEAR
WARRANTY

DIMMABLE



| CODE | DESCRIPTION | TECHNICAL DATA | | | | DIMENSIONS | | |
|---------------------|------------------------|----------------|------------|-------------|----------|-------------|------------|------------|
| | | BASE | KELVIN (K) | LUMENS (LM) | WATT (W) | LENGTH (mm) | WIDTH (mm) | CARTON QTY |
| CLAESH12V14W | 14W G4 ESH HALOGEN | G4 | 2800 | 160 | 14=20 | 30 | 9.5 | 100/1K |
| CLAESH12V20W | 20W GY6.35 ESH HALOGEN | GY6.35 | 2800 | 300 | 20=35 | 40 | 11 | 100/1K |
| CLAESH12V35W | 35W GY6.35 ESH HALOGEN | GY6.35 | 2800 | 600 | 35=50 | 40 | 11 | 100/1K |
| CLAESH12V40W | 40W GY6.35 ESH HALOGEN | GY6.35 | 2800 | 640 | 40=60 | 38 | 10 | 100/1K |

BI-PIN HALOGEN GLOBES

- Input voltage: 6V & 12V
- Specially suitable for chandeliers and small fittings
- Can be used indoors and outdoors in a waterproof fitting
- Suitable for dimming

2,000
HRS

1 YEAR
WARRANTY

DIMMABLE



| CODE | DESCRIPTION | TECHNICAL DATA | | | | DIMENSIONS | | |
|----------------|----------------------|----------------|------------|-------------|----------|-------------|------------|------------|
| | | BASE | KELVIN (K) | LUMENS (LM) | WATT (W) | LENGTH (mm) | WIDTH (mm) | CARTON QTY |
| JC6V10W | JC 6V G4 10W HALOGEN | G4 | 2800 | 115 | 10 | 33 | - | 100/1K |

Brochure updated on 14.12.2016