



SINGLE ENDED METAL HALIDE GLOBES

- Input voltage: 240V AC with control gear
- Wattage: 35W, 70W & 150W
- Reduced UV output
- Excellent colour rendering
- High intensity light output

10,000
HRS

1 YEAR
WARRANTY



CODE	DESCRIPTION	TECHNICAL DATA				DIMENSIONS	
		BASE	KELVIN (K)	LUMENS (LM)	WATT (W)	LENGTH (mm)	CARTON QTY
35W							
CLAMHS35W4000K	35W G12 SINGLE ENDED MH 4000K	G12	4000	2450	35	95	1/12
CLAMHS35W5000K	35W G12 SINGLE ENDED MH 5000K	G12	5000	2450	35	95	1/12
70W							
CLAMHS70W3000K	70W G12 SINGLE ENDED MH 3000K	G12	3000	4550	70	95	1/12
CLAMHS70W4000K	70W G12 SINGLE ENDED MH 4000K	G12	4000	4550	70	95	1/12
CLAMHS70W5000K	70W G12 SINGLE ENDED MH 5000K	G12	5000	4550	70	95	1/12
150W							
CLAMHS150W3000K	150W G12 SINGLE ENDED MH 3000K	G12	3000	10500	150	95	1/12
CLAMHS150W4000K	150W G12 SINGLE ENDED MH 4000K	G12	4000	10500	150	95	1/12
CLAMHS150W5000K	150W G12 SINGLE ENDED MH 5000K	G12	5000	10500	150	95	1/12

Brochure updated on 14.12.2016