

## **PRODUCT FEATURES**

- Input voltage: 12-25V DC / AC
- External Control Gear Required
- Max 20W Halogen Globe
- Globe not included
- Fixed MR16 Lampholder
- Recommended CLA LED globes: MR1601 and MR1602
- Material: 316 Stainless steel
- Plastic sleeve included (must be installed)
- Fitting slides into sleeve and remains unattached
- Cable included (L950mm)
- 4mm tempered glass, max load capacity 100kg









IGM2SS



IGM3SS

**IGM4SS** 

PART NO.	DESCRIPTION	COLOUR	WEIGHT (KG)	вох (см)	CARTON QTY
IGM1SS	INGROUND / WALL 1 WAY MR16 12V SS316 RND	316 Stainless steel clear anodized	0.4	13 x 10 x 10	20
IGM2SS	INGROUND / WALL 2 WAY MR16 12V SS316 RND	316 Stainless steel clear anodized	0.4	13 x 10 x 10	20
IGM3SS	INGROUND / WALL 3 WAY MR16 12V SS316 RND	316 Stainless steel clear anodized	0.4	13 x 10 x 10	20
IGM4SS	INGROUND / WALL 4 WAY MR16 12V SS316 RND	316 Stainless steel clear anodized	0.4	13 x 10 x10	20

Sleeve: OD 70mm

UPDATED ON 22.03.2018

Tel: (02) 9938 7100 | Fax: (02) 9938 7115 | Email: sales@clalighting.com.au Website: www.clalighting.com.au Follow us: facebook.com/CLALighting

