


# MR11 LED GLOBES

## Product Features:

- Input voltage: 12V AC/DC
- Heatsink: aluminium
- Wattage: 4W=30W Incandescent globe
- LED chips: 3pcs SMD2835
- CRI: >80
- Power factor:  $\geq 0.5$
- Ambient temperature: -20 to 50°C
- Not suitable for dimming
- Suitable for 2 way switching
- Suitable for use with sensors
- Remote control gear required



Part No.	Description	Base	Kelvin	Lumens	Wattage	PF	Dimensions	Box Weight	Box Dimensions	Carton QTY
MR1101	GLOBE LED 12V GU4 AC/DC MR11 4W 3000K	GU4	3000K	260LM	4W	$\geq 0.5$	Ø34.8X38.5mm	0.03kg	4x4x5cm	1/10/100
MR1102	GLOBE LED 12V GU4 AC/DC MR11 4W 5000K	GU4	5000K	260LM	4W	$\geq 0.5$	Ø34.8X38.5mm	0.03kg	4x4x5cm	1/10/100

## Tested and recommended drivers:

BRAND	PART NO.	TYPE	IP RATING
CLA	CLADR12W	LED Driver (Constant Voltage)	IP20
CLA	DRIV1	LED Driver (Constant Voltage)	IP20
CLA	OTTER1	LED Driver (Constant Voltage)	IP67
CLA	CLA111011	LED Driver (Constant Voltage)	IP67
CLA	CLA113011	LED Driver (Constant Voltage)	IP67
CLA	CLA115011	LED Driver (Constant Voltage)	IP67
CLA	CLA1110011	LED Driver (Constant Voltage)	IP67
CLA	CLA1115011	LED Driver (Constant Voltage)	IP67
CLA	CLA1120011	LED Driver (Constant Voltage)	IP67
LUXMAN	ETH50.302VA	Transformer	IP65