



# **SJS1500**SJS+Smart Jump Start Charger

16,000mAh (60Whr) LITHIUM POLYMER BATTERY CELL





# Will jump start MOST vehicles:

Up to 4.2L(4200cc) DIESEL Up to 7.0L(7000cc) PETROL



### Zip carry case contents:

- 12V 16,000mAh (60Whr) Lithium Polymer Power Pack
- Insulated Jump Start Safe Jumper Leads
- 240V AC/15V DC 1A Wall Charger
- 12V DC/15V DC 1A car charger
- USB 2 in 1 Adaptor cable
- User manual and Instruction cards

## **NEW Features:**

Jumper leads with advanced

JUMP START SAFETM

Technology fully automatic with VOLTAGE DETECTION SAFETY PROTECTION.

- LCD display screen to show BATTERY CAPACITY
- Ultra compact and lightweight design

### **Technical data:**

- Size: L: 185mm W: 85mm H: 38mm (Power Pack only)
- Weight: 550g (Power Pack only)
- Battery: 12V Lithium Polymer 16,000mAh (60 Whr) 3S
- Max. Current: 1500A Absolute . 600A PEAK at clamps 300A START at clamps
- Output: Jump Port 2V DC
- Device powering 12V DC up to 180watts. Use SSCFCL156 Adaptor (Sold seperately)
- Digital Charging Ports: USB x2 / 5V 2.1A x1 / 5V 1A x1
- Battery Chargers: AS approved 240V AC/15V 1A DC. 12V DC/15V DC 1A Car Charger
- Recharge Time: 4 hrs from flat with 240V charger, 8hrs with Car charger
- Charge Indictator: Backlit LCD Diisplay screen
- Self Discharge Rate: approx. 0.2V per month depending on ambient storage temperature
- Protection & Safety: Reverse Current, Reverse Polarity, Short Circuit, Overtemp, Overcranking, Surge,

Voltage Differential, Overload Reset, Over Charge, Over Discharge

- **LED Flashlight:** 3 Mode , Full , S.O.S , Emergency Flash
- Operating Temperature Range: -20 deg C to 60 deg C

UPDATED ON 06/02/2018











Tel: (02) 9938 7100 | Fax: (02) 9938 7115 | Email: sales@clalighting.com.au

Website: www.clalighting.com.au

Follow us: facebook.com/CLALighting







# SJS1500TP

SJS+Smart Jump Start Charger with tyre pump


16,000mAh (60Whr) LITHIUM POLYMER BATTERY CELL





# Will jump start MOST vehicles:

Up to 4.2L(4200cc) DIESEL Up to 7.0L(7000cc) PETROL



### Zip carry case contents:

- 12V 16,000mAh (60Whr) Lithium Polymer Power Pack
- Insulated Jump Start Safe Jumper Leads
- 240V AC/15V DC as Approved Wall Charger
- 12V DC/15V DC car charger
- USB 2 in 1 Charging cable
- User manual and Instruction cards

## **NEW Features:**

• Jumper leads with advanced

JUMP START SAFETM

Technology fully automatic with VOLTAGE DETECTION SAFETY PROTECTION.

- LCD display screen to show BATTERY CAPACITY
- Ultra compact and lightweight design

### **Technical data:**

- Size: L: 185mm W: 85mm H: 38mm (Power Pack only)
- Weight: 550g (Power Pack only)
- Battery: 12V Lithium Polymer 16,000mAh (60 Whr) 3S
- Max. Current: 1500A Absolute . 600A PEAK at clamps 300A START at clamps
- Output: Jump Port 2V DC
- Device powering 12V DC up to 180watts. Use SSCFCL156 Adaptor (Sold seperately)
- Digital Charging Ports: USB x2 / 5V 2.1A x1 / 5V 1A x1
- Battery Chargers: AS approved 240V AC/15V 1A DC. 12V DC/15V DC 1A Car Charger
- Recharge Time: 4 hrs from flat with 240V charger, 8hrs with Car charger
- Charge Indictator: Backlit LCD Diisplay screen
- Self Discharge Rate: approx. 0.2V per month depending on ambient storage temperature
- Protection & Safety: Reverse Current, Reverse Polarity, Short Circuit, Overtemp, Overcranking, Surge,

Voltage Differential, Overload Reset, Over Charge, Over Discharge

- **LED Flashlight:** 3 Mode , Full , S.O.S , Emergency Flash
- Operating Temperature Range: -20 deg C to 60 deg C

UPDATED ON 30/01/2018











Tel: (02) 9938 7100 | Fax: (02) 9938 7115 | Email: sales@clalighting.com.au

Website: www.clalighting.com.au

Follow us: facebook.com/CLALighting

