

SLICKTRI

LED Dimmable **ULTRA SLIM** Recessed Downlights


TRI-CCT 3000K 4000K 5000K

- Input voltage range: 220-240V
- Remote constant current driver included
- Housing & faceplate: PC
- Diffuser: white PS
- Tri-CCT (3000K/ 4000K/ 5000K) in one fitting
- CCT switch on DC cable
- LED chips: SMD2835
- Power factor: 0.9
- CRI: >80
- Flex & plug: 1.2m
- Ambient temperature: -20 to 40°C
- Suitable for dimming
- Suitable for 2-way switching
- Suitable for use with Microwave & motion sensor




General Lighting


30,000hr Lifetime	110° Beam Angle	IP40 Rated	DIMMABLE	3YEAR Replacement Warranty
-------------------	-----------------	------------	----------	----------------------------




SLICKTRI1R




SLICKTRI1S




SLICKTRI2R



SLICKTRI2S



SLICKTRI3R



SLICKTRI3S

Tested & Recommended Dimmers:

BRAND	PART NO.	PCS PER DIMMER
CLA	VELA	
CLIPSAL	32E450UDM, 31E2PUDM, 32ELED-DWE, 32E450TM, PDL354PBDMUN-VW	SLICKTRI1R: 2-11PCS SLICKTRI2R: 2-8PCS SLICKTRI3R: 2-5PCS SLICKTRI1S: 2-11PCS SLICKTRI2S: 2-8PCS SLICKTRI3S: 2-5PCS
HPM	Cat 250T, Cat 400T	
Diginet	MEDM, MMDM/RT	

PART NO.	DESCRIPTION	LUMENS (LM)			WATT (W)	DRIVER SIZE (MM)	SWITCH SIZE (MM)	BOX WEIGHT	BOX SIZE (CM)	CARTON QTY
		3000K	4000K	5000K						
SLICKTRI1R	D/L LED FIXED DIMM SLIM WH RND TRI	630	720	680	9	80x31x20	45x23x15	0.31kg	19x45x16	1/40
SLICKTRI2R	D/L LED FIXED DIMM SLIM WH RND TRI	840	960	900	12	87x37x20	45x23x15	0.38kg	19x45x18.5	1/40
SLICKTRI3R	D/L LED FIXED DIMM SLIM WH RND TRI	1350	1550	1450	18	87x37x20	45x23x15	0.5kg	25.5x45x23.5	1/20
SLICKTRI1S	D/L LED FIXED DIMM SLIM WH SQ TRI	630	720	680	9	80x31x20	45x23x15	0.34kg	21x45x16	1/40
SLICKTRI2S	D/L LED FIXED DIMM SLIM WH SQ TRI	840	960	900	12	87x37x20	45x23x15	0.4kg	23x45x18.5	1/40
SLICKTRI3S	D/L LED FIXED DIMM SLIM WH SQ TRI	1350	1550	1450	18	87x37x20	45x23x15	0.6kg	28x45x23.5	1/20