




**DIMMABLE SURFACE SERIES**  
LED Surface Mounted Ceiling Lights IP65



**Product Features**

- Input voltage: 240V AC 50/60Hz
- Wattage: 13W
- Material: aluminium
- Epistar COB LED chip
- Power factor: 0.9
- Ambient temp: -20 to 40°C
- Suitable for dimming
- Recommended Universal Trailing Edge and Leading Edge dimmers
- Suitable for 2-way switching
- 3 year replacement warranty

35,000 HRS | BEAM 40° | IP 65 | 3 YEAR WARRANTY | DIMMABLE

**Recommended dimmers: (2-8 pcs /dimmer)**

- (1) CLA LYNX
- (2) CLA-VELA
- (3) Clipsal 32ELEDM
- (4) Clipsal 31E2PUDM
- (5) Clipsal 32E450UDM
- (6) Clipsal 32E450LM
- (7) HPM CAT250L
- (8) HPM CAT250T
- (9) HPM CAT400T

Technical data												
CODE	DESCRIPTION	KELVIN (K)	LUMENS (LM)	WATT (W)	CRI	BEAM ANGLE	IP	DIMM	DIAM (mm)	DEPTH (mm)	CARTON QTY	
<b>SURFACE13</b>	13W GLOSS WH LED S/M CEILING LIGHT 3000K	3000	800	13	>80	40°	IP65	YES	Ø105	146	1/12	
<b>SURFACE14</b>	13W GLOSS WH LED S/M CEILING LIGHT 5000K	5000	900	13	>80	40°	IP65	YES	Ø105	146	1/12	
<b>SURFACE15</b>	13W GLOSS BLK LED S/M CEILING LIGHT 3000K	3000	800	13	>80	40°	IP65	YES	Ø105	146	1/12	
<b>SURFACE16</b>	13W GLOSS BLK LED S/M CEILING LIGHT 5000K	5000	900	13	>80	40°	IP65	YES	Ø105	146	1/12	

UPDATED ON 09.10.2018