

EGLO EXPERT



EXPERT DOWNLIGHT
208024N-6W DOWNLIGHT/CCT DIP SWITCH

EGLO Lighting Australia
Made in China


Thank you for purchasing a quality EGLO EXPERT downlight. Please read the following instructions carefully before installation. Keep this document for future reference.

WARNING!


Any electrical wiring must be carried out by a licensed electrician or qualified personnel. Installation must follow all relevant Australian wiring rules & standards.

INSTALLATION


Images are for reference only.




1 Turn power off at main electrical supply board.




2 Ensure that there are no cables or pipes in the ceiling cavity above where the downlight is to be installed. Using a 70 mm hole saw, carefully cut a hole in the plaster. Use appropriate eye protection, dust mask and appropriate safety apparatus to ensure adequate personal protection.




3 For model number 208024N (colour temperature selection switch on back of fitting), set the desired colour temperature (3000K, 4000K or 5000K) by toggling the switch on the back of the downlight BEFORE installation.




4 Insert the plug into the power socket located in the ceiling. Please note, if no power socket is present, one will need to be installed by a licenced electrician.



5 Fold the two side springs back against the down light body simultaneously, whilst inserting into the pre-cut hole. Once inside the hole, the springs should naturally tense back down onto the top of the plaster ceiling to hold the downlight firmly in place.



6 This downlight has been tested and has achieved an IC-4 thermal rating, meaning it can be abutted and covered with thermal insulation in normal use. The minimum clearance distance from the luminaire to any normally flammable building element is 0mm. The minimum clearance distance from the top of the luminaire to any building insulation is 0mm.



7 Turn the power on at the mains supply board.

YOUR DOWNLIGHT/S ARE NOW READY FOR USE.



EGLO Lighting Australia
5/339 Archerfield Road,
Richlands, Queensland 4077
Made in China
www.eglo.com.au

Protection: Class II, IP44 (From the front of fitting when mounted)
Voltage: 220-240V 50/60Hz
Max Power: 6W including driver
Illuminant: This item includes an integrated LED board which is non-replacable
Colour Temperature: Switchable between 3000K, 4000K & 5000K (model 208024N)

DISPOSAL

WARNING-RISK OF FIRE, BURNS AND OTHER INJURIES

The luminaires may become hot during use. Do not touch them. Never hang anything over it.

If the external flexible cable or cord of this luminaire is damaged, it shall be exclusively replaced by the manufacturer or his service agent or a similar qualified person in order to avoid a hazard.

The light source of this luminaire is not replaceable; when the light source reaches its end of life the whole luminaire shall be replaced.

ANY NOTES

This image shows a full page of blank graph paper. The grid consists of small squares formed by thin gray lines. The top-left and bottom-left corners of the page are rounded, while the right side remains straight. There are no margins, text, or other markings on the page.