



General Information

Material number	20537801
EAN/UPC	9008606239177
Type	ceiling fan & light

Dimensions

Article Diameter (in mm)	1320
Article Height (in mm)	338
Canopy Height (in mm)	66
Canopy Diameter (in mm)	152
Net Weight (in kg)	5.6 Kilogram
Gross Weight	6.8 Kilogram
Single-Box Height (in mm)	250
Single-Box Length (in mm)	700
Single-Box Depth (in mm)	325

Fan

Motor Type	DC
Motor dimension in MM (Ø x H)	132,5 x 10
Motor Wattage	70
Adjustable Canopy	13°
Blade pitch in degree	Variable
Blade Quantity	3
Protection Degree	IP20
Mains Voltage	220-240V, 50Hz

Material & Colour






Blade Material	ABS
Blade Colour (1)	white matt
Canopy Material	ABS
Canopy Colour	white matt
Enclosure Material	ABS
Enclosure Colour	white matt
Glass/Shade Material	acrylic
Glass/Shade Colour	milky

Performance

Wattage by air movement (1)	3.3
RPM (1)	70
Air Movement m3/Hr (1)	2894
Wattage by air movement (2)	5.5
RPM (2)	105
Air Movement m3/Hr (2)	4860
Wattage by air movement (3)	10
RPM (3)	140
Air Movement m3/Hr (3)	6690
Wattage by air movement (4)	15.5
RPM (4)	170
Air Movement m3/Hr (4)	8740
Wattage by air movement (5)	27
RPM (5)	200
Air Movement m3/Hr (5)	10100
Wattage by air movement (6)	40
RPM (6)	230
Air Movement m3/Hr (6)	12640

Illuminant

Illuminant Type (1)	LED
max. Wattage (1)	20W
Light colour Complete	TUNEABLE WHITE

				
12640 m ³ /h	13°	0W	AAA, Alkali, LR03, 1,5V	Micro

20537801
ILUKA



Technical changes reserved

3/3



Contact | Support
eglo.com/en/eglo-worldwide



General Information

Material number	20537802
EAN/UPC	9008606239184
Type	ceiling fan & light

Dimensions

Article Diameter (in mm)	1320
Article Height (in mm)	338
Canopy Height (in mm)	66
Canopy Diameter (in mm)	152
Net Weight (in kg)	5.6 Kilogram
Gross Weight	6.8 Kilogram
Single-Box Height (in mm)	250
Single-Box Length (in mm)	700
Single-Box Depth (in mm)	325

Fan

Motor Type	DC
Motor dimension in MM (Ø x H)	132,5 x 10
Motor Wattage	70
Adjustable Canopy	13°
Blade pitch in degree	Variable
Blade Quantity	3
Protection Degree	IP20
Mains Voltage	220-240V, 50Hz

Material & Colour






Blade Material	ABS
Blade Colour (1)	black matt
Canopy Material	ABS
Canopy Colour	black matt
Enclosure Material	ABS
Enclosure Colour	black matt
Glass/Shade Material	acrylic
Glass/Shade Colour	milky

Performance

Wattage by air movement (1)	3.3
RPM (1)	70
Air Movement m3/Hr (1)	2894
Wattage by air movement (2)	5.5
RPM (2)	105
Air Movement m3/Hr (2)	4860
Wattage by air movement (3)	10
RPM (3)	140
Air Movement m3/Hr (3)	6690
Wattage by air movement (4)	15.5
RPM (4)	170
Air Movement m3/Hr (4)	8740
Wattage by air movement (5)	27
RPM (5)	200
Air Movement m3/Hr (5)	10100
Wattage by air movement (6)	40
RPM (6)	230
Air Movement m3/Hr (6)	12640

Illuminant

Illuminant Type (1)	LED
max. Wattage (1)	20W
Light colour Complete	TUNEABLE WHITE

 AIRFLOW	 HANG SURE CANOPY	 LED	 ACCU	 Micro
12640 m ³ /h	13°	0W	AAA, Alkali, LR03, 1,5V	

20537802
ILUKA



Technical changes reserved

3/3



Contact | Support
eglo.com/en/eglo-worldwide



General Information

Material number	20537815
EAN/UPC	9008606239191
Type	ceiling fan & light

Dimensions

Article Diameter (in mm)	1320
Article Height (in mm)	338
Canopy Height (in mm)	66
Canopy Diameter (in mm)	152
Net Weight (in kg)	5.6 Kilogram
Gross Weight	6.8 Kilogram
Single-Box Height (in mm)	250
Single-Box Length (in mm)	700
Single-Box Depth (in mm)	325

Fan

Motor Type	DC
Motor dimension in MM (Ø x H)	132,5 x 10
Motor Wattage	70
Adjustable Canopy	13°
Blade pitch in degree	Variable
Blade Quantity	3
Protection Degree	IP20
Mains Voltage	220-240V, 50Hz

Material & Colour






Blade Material	ABS
Blade Colour (1)	brown rustic
Canopy Material	ABS
Canopy Colour	black matt
Enclosure Material	ABS
Enclosure Colour	black matt
Glass/Shade Material	acrylic
Glass/Shade Colour	milky

Performance

Wattage by air movement (1)	3.3
RPM (1)	70
Air Movement m3/Hr (1)	2894
Wattage by air movement (2)	5.5
RPM (2)	105
Air Movement m3/Hr (2)	4860
Wattage by air movement (3)	10
RPM (3)	140
Air Movement m3/Hr (3)	6690
Wattage by air movement (4)	15.5
RPM (4)	170
Air Movement m3/Hr (4)	8740
Wattage by air movement (5)	27
RPM (5)	200
Air Movement m3/Hr (5)	10100
Wattage by air movement (6)	40
RPM (6)	230
Air Movement m3/Hr (6)	12640

Illuminant

Illuminant Type (1)	LED
max. Wattage (1)	20W
Light colour Complete	TUNEABLE WHITE

				
12640 m ³ /h	13°	0W	AAA, Alkali, LR03, 1,5V	Micro

20537815
ILUKA



Technical changes reserved

3/3



Contact | Support
eglo.com/en/eglo-worldwide