


Cougar Lighting Pty Ltd

Product Specification Sheet

Name	FAHRENHEIT	Checked
Model Number	FAH18WPL	
Description	Fahrenheit PL 18W Wall Light	
Finish	Chrome (Steel)	
Glass	2 x Frost Glass Panel L: 315mm W: 64mm 4mm thick	

COMPONENT VERIFICATION

Component	Manufacturer	Model No	Technical Data	Standard	Marks of Conformity	
Lampholder	Ningbo Economic & Technical	2G11	AC 250V, 2A, 140°C, Screwless Terminal	Annex 1 of Council Directive 2006/95/EC	TUV	
Terminal Block	Heavy Power Co Ltd	PA7	White Plastic 3 Pole 450V 17.5A	EN 60998-2-1:2004	VDE CERT NO: 40019839	
Earth Internal Wiring Active & Neutral	Shenzhen Mysun Insulation Materials	HO5S-K	Silicon Rubber, 1 x 0.75mm ² , 450V, 180°C	DIN VDE 0282:2005-02	VDE CERT NO: 40016705	
	Guangzhou Feng Tai Electronics	FT-FEP-102 VDE REG NO:7997	Single Core 1 x 0.5mm ² 300/500V	EN 60228:2005	VDE CERT NO: 40013289	
Driver/Ballast	SELF ELECTRONICS	SBG1X18/PLN1	Electronic Ballast 220-240V, 50/60Hz, 0.12A	AS/NZS 61347.2.3:2004	SAA: TUV15153EA C- TICK: N2816	
Globe supplied	Xieguang Electronics Co. Ltd	H-18	Single Capped 18W 2700k	EN55015:2000+A1:2001 EN61547:1995+A1:2000	CE	

Globe Description	PL 18W 2700k (Compact 2 Tube) TC-L					
Relamping Label	PL 18W MAX (On backplate next to tube)					
Dimensions	Backplate H: 60mm W: 32mm L: 240mm H: 60mm W: 70mm L: 322mm Overall H: 60mm L: 322mm P: 100mm					Housing:
Wiring Layout	Double insulated single core active & neutral conductors only , from terminal block to the ballast. Double insulated single core active & neutral conductors only from the ballast to the lamp holder. Active & neutral conductors have white heat protective shrink covering them. Earthed from the backplate to the terminal block. Earth wire must be BRASS CRIMPED. NO SOLDER					
Mounting & Construction	Metal rail that mounts to wall holds to the backplate by 2crews. 2 x Frost glass panels that cover the PL lamp & lampholder, top and bottom, held to the chrome housing by chrome screws. The PL ballast is mounted inside the backplate.					
IP Rating	N/A					
Weather Proofing	N/A					
Drainage Hole	N/A					
Cable Entry Hole	19mm hole in white metal mounting rail, white rubber grommet 18mm.					
Labels	<p>1. Rating Label</p> <div style="border: 1px solid black; padding: 10px; text-align: center;"> <p>COUGAR LIGHTING</p> <p>MODEL NO: FAH18WPL</p> <p>240V 50Hz MAX PL 18 WATT</p> <p>THIS LUMINAIRE MUST BE INSTALLED</p> <p>BY A LICENSED ELECTRICIAN</p> <p>MADE IN CHINA</p> </div> <p>2. IP Integrity Label N/A</p> <p>3. AEN Label Imprinted on black plastic pad underneath terminal block.</p> <p>4. Earth Label Earth label is to be placed close to the earth wire internally</p> <p>Label Position 1. The Rating Label ,4. Earth Label should all be mounted inside the backplate. 3. AEN Label should be on plastic terminal block pad.</p>					
Packing	2 Ply White box with 30cm x 10cm colour label. Fitting packed in plastic bag. Polystyrene inside box.					
Barcode	9305125007042					
Accessory	2 x plaster screws.					
Instructions	Yes					
Design Specification	AS/NZS 60598.2.1					
Warranty	12 month (excluding tube).					

Image:

Comments:

- 1) ALL WIRING MUST AS SPECIFIED.
- 2)SELF PL BALLAST MUST HAVE OUR RCM LOGO ON IT.
- 3) NO SOLDER TO BE USED ON ENDS OF WIRING.
- 4) MUST BE EARTHED AS PER OUR WIRING INSTRUCTIONS ABOVE.



Checked

