

Important Safety Issues;

- This product must be installed by a qualified electrician according to AS/NZS 3000.
- Ensure all electrical mains are disconnected before any installation.
- Modification of this product will void any warranty.
- Havit Lighting does not take responsibility for wrong installation, incorrect use, or use of installation material that does not belong to the system.
- For low voltage models a minimum 2.5mm low voltage garden cable must be used with a minimum 0.02mm copper strand size. (warranty will be voided if any other type of cable is used.)
- All o-rings and seals must be in place correctly to maintain warranty .

Steps for Installation;

1. Make sure that the electrical circuit is free of voltage (master switch off)
2. Remove the face from backing plate with philips head screw driver
3. Install the backing plate securely, ensuring to seal around this plate to avoid moisture penetration. Seal all holes in the backing plate including cable entry and screw holes. Failure to do so will void warranty.
4. Connect the cable -
 - 240v models, (use wire with earth); connect the earth first, then live and neutral wire.
5. Choose colour temperature by sliding switch to desired colour temperature. (see diagram 1)
6. Affix the face of the fitting to the backing plate.
7. Apply silicon around baseplate to avoid water ingress.
8. All connections must be carried out carefully, inspect all contacts before switching back on the electric circuit.




diagram 1

THESE FITTINGS MUST BE INSTALLED BY A LICENSED ELECTRICIAN