




HV3630



HV3631



HV3632



Important Safety Issues:

- This product must be installed by a qualified electrician according to AS/NZS 3000.
- Ensure all electrical mains are disconnected before any installation.
- Modification of this product will void any warranty.
- Havit Lighting does not take responsibility for wrong installation, incorrect use, or use of installation material that does not belong to the system.
- For low voltage models a minimum 2.5mm low voltage garden cable must be used with a minimum 0.02mm copper strand size. (warranty will be voided if any other type of cable is used.)
- All o-rings and seals must be in place correctly to maintain warranty.

Steps for Installation:

1. Make sure that the electrical circuit is free of voltage (master switch off)
2. Connect the cable -
 - a. 240v models, (use wire with earth); connect the earth first, then live and neutral wire
3. Install the backing plate securely, ensuring to seal around this plate to avoid moisture penetration. Seal all holes in the backing plate including cable entry and screw holes.
Failure to do so will void warranty.
4. Insert lamps into lampholder (see max wattage info)
5. Affix the spotlight to the mounting plate by tightening screws with philips head screwdriver.
6. Attach face to backing plate and tighten screws making sure they are tightened correctly.
7. All connections must be carried out carefully, inspect all contacts before switching back on the electric circuit.

Lamp Changing

1. Undo screws from fitting.
2. Slide fitting off backing plate.
3. Take out globes by twisting anti-clockwise.
4. Reinsert globe by twisting clockwise
5. Reattach face to backing plate
6. Screw fitting to backing plate.

THESE FITTINGS MUST BE INSTALLED BY A LICENSED ELECTRICIAN