

Muovi Wall or Ceiling Light Installation Instructions



Product Specifications

Model No.	HV3523T-BLK	HV3523T-WHT	HV3525T-BLK	HV3525T-WHT	HV3526T-BLK	HV3526T-WHT	HV3527T-BLK	HV3527T-WHT
Name	Muovi							
Material	Full Polycarbonate Body and Diffuser							
Colour	Black	White	Black	White	Black	White	Black	White
Installation Type	Wall or Ceiling							
IP Rating	IP54							
Input Voltage	240v AC							
Protection Class	2 (No Earth Required) <input type="checkbox"/>							
Lamp Base	Built in LED							
Lamp Wattage	1x 7w		1x 12w		1x 5w		1x 7w	
Colour Temp	TRI Colour - 3000k, 4000k, 5500k							
Lumens	540lm, 610lm, 550lm		975lm, 1070lm, 1000lm		435lm, 475lm, 445lm		575lm, 630lm, 585lm	
CRI	> 80							
Wiring	Parallel							
Dimmable	No							
Warranty	3 Years Replacement*							

HV3523T Dimensions	HV3525T Dimensions	HV3526T Dimensions	HV3527T Dimensions

Important Safety Issues:

- This product must be installed by a qualified electrician according to AS/NZS 3000.
- Ensure all electrical mains are disconnected before any installation.
- Modification of this product will void any warranty.
- Havit Lighting does not take responsibility for wrong installation, incorrect use, or use of installation material that does not belong to the system.
- Aluminium and 304SS fittings must not be installed within 5km of any salt water environments.
- All o-rings and seals must be in place correctly to maintain warranty
- This form may be updated at any time due to product improvements, please check online installation form for most current version.

Steps for Installation:

1. Make sure that the electrical circuit is free of voltage (master switch off)
2. Connect the cable - Connect live and neutral wires from wall or ceiling to cables at back of fitting. NOTE: Cable cannot be connected internally in fitting, Must be connected externally
3. Cover connections using an adhesive lined heat shrink or gel cap to make connection watertight. Failure to do this will void warranty.
4. Heat the heat shrink or crimp the gel cap making sure all connections are covered.
5. Fitting is preset to 3000k, to change slide switch located at back of fitting to desired colour temperature..
6. Place fitting in location to be installed and attach to wall or ceiling with screws supplied through holes on edge of fitting
7. Apply silicon around edge of fitting to prevent any water from getting inside to electrical connections.
8. All connections must be carried out carefully, inspect all contacts before switching back on the electric circuit.

Must be installed by a licensed electrician

Contact Details:

143 Beauchamp Road
Matraville NSW 2036
Australia

Tel: 02 9381 8300
Fax: 02 9666 8881
Email: sales@havit.com.au
Web: www.havit.com.au

Warranty Terms & Conditions*



www.havit.com.au

