

## **PRODUCT SPECIFICATIONS:**

**Light Source:** 5050 SMD LED

**Number Of LED Per Metre:** 30

**CRI:** ≥80

**Wattage per Metre:** 7.2w

**Dimmable:** Yes (using Havit RGB LED Controllers)

**Maximum Continuous Run:** 4 metres

**Additional Requirements:** 12v DC Constant Voltage LED Driver

**Mounting:** Must be mounted on either Aluminium Heat Sink or Aluminium Profile.

**Warranty:** 2 years replacement\*\*



IP20



IP54



IP67

PART NUMBER	SIZE	LUMENS* PER METRE	INPUT VOLTAGE	BEAM ANGLE	IP RATING	CUTTING INCREMENTS
HV9750-IP20-30-RGB	10mm x 2mm	585lm (white)	12v DC	120°	IP20	every 100mm
HV9750-IP54-30-RGB	10mm x 3mm	585lm (white)	12v DC	120°	IP54	every 100mm
HV9750-IP67-30-RGB	12mm x 4mm	585lm (white)	12v DC	120°	IP67	every 100mm

Must be used with suitable 12v DC LED driver and RGB Controller

\* Lumen output measured at source

\*\* See Warranty Terms and Conditions for more information

*For more information contact Havit Lighting*

ADDRESS:  
143 Beauchamp Road  
Matraville NSW 2036  
Australia

Tel: 02 9381 8300  
Fax: 02 9666 8881  
Email: sales@havit.com.au  
web: www.havit.com.au