

### MOON SURFACE MOUNTED

Variants		Item No.	Colour Temp
Blk	Wht		
22812	22813	MOON-SM	TRIO
22814	22815		
22816	22817		
22818	22819		
			FLD
			OPAL
			SPOT
			TUBE

Thank you for purchasing your new MOON-SM Light, Please take the time to read and understand the instruction sheet below. Failure to do so may void warranty.

### Specifications

Voltage:	240V	CCT:	3000K - 4000K - 5700K (Switchable)	Dimmable:	Yes	Lifespan:	50,000hrs
Power:	6/9W	IP Rating:	20	CRI:	>80		

Please refer to the data sheet for lumen output.

Optional Optics:				
01 Flood	02 Spot	03 Opal	04 Tube	
<p>1 Select suitable CCT / Power you need.</p>	<p>2 Select the optics, then lock the safety wire.</p>	<p>3 Rotate the optics on the LED engine in clockwise direction, make sure it was locked until you hear "click".</p>	<p>4 Take out the faceplate.</p>	
<p>5 Turn off the power.</p>	<p>6 Use the faceplate to position on the ceiling.</p>	<p>7 Drill the hole on the ceiling.</p>	<p>8 Mounted plastic expansion screws.</p>	
<p>9 Fixed the faceplate.</p>	<p>10 Connect L/N wires.</p>	<p>11 Tighten the screws to fix the surface base.</p>	<p>12 Adjust the direction as required.</p>	<p>13 Turn on the power.</p>

**Note:** -The lamp must be installed by professional electrician  
-Ensure the power supply is switched off before fitting this product

-Do not touch the lamp when in use  
-Keep away from hot steam and corrosive gas