

29-31 Richland St. Kingsgrove. Sydney NSW 2208 Australia

Phone: 02 9554 9600 | Fax: 02 9554 9433

Date: 02/2021

enquiries@domuslighting.com.au | www.domuslighting.com.au

## Installation Manual

## Pico 3 Tilt

|               | Variants |             |             |  |
|---------------|----------|-------------|-------------|--|
| Blk           | Wht      | Item No.    | Colour Iemp |  |
| 21577         | 21578    | PICO-3-TILT | TRIO        |  |
| <b>TI I</b> ( | c 1      |             |             |  |

Thank you for purchasing your new PICO-3-TILT Downlight, Please take the time to read and understand the instruction sheet below. Failure to do so may void warranty.

## Specifications

| Voltage:  | 240V | Lumen (±5%): | Warm White 3000K - 180lm<br>Neutral White 4000K - 210lm<br>White 5700K - 210lm | Dimmable: | Yes       |  |  |  |
|---|------|--------------|--|-----------|-----------|--|--|--|
| Power:  | 3W   | Beam Angle:  | 24°  | CRI:      | ≥80       |  |  |  |
| IP Rating:  | 40   | CCT:         | 3000K - 4000K - 5700K (Switchable)   | Lifespan: | 50,000hrs |  |  |  |
| Black model is 10% lower in lumen output compared to the white model. |      |              |  |           |           |  |  |  |

