



PREMIER S9075TC DP - 23/30W

IP64 30W LED downlight with selectable CCT and power

Application

Ideal for any residential or commercial interior space requiring flexibility in power selections

Design Specifications


- Premium aluminium body profile, CA90 rated
- Stylish white powder coat finish
- Quality opal polycarbonate diffuser
- High efficiency LED optics
- Remote constant current non-dimmable LED driver, with flex and plug

Performance

- Dimmable - **OPTIONAL**
- Dimmer Type - **Trailing edge, 1-10V, DALI/DSI**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Multiple Wattage	Lumens (lm)	CCT (K)	Beam Angle (°)
	S9075TC/WH/DP	240	23/30	2600/3100/2800	3000/4000/5700	90

Dimmable	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)	VEET
OPTIONAL	80	WHITE	195	230	75(H)	YES

Note: Lumens (lm) shown are at FULL power


Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



Dimensions



Dimensions




Photometric Data

Photometric Data

Unit: cd C0/C180 — C90/C270 —

S9075TC/WH/DP at 4000K



THE SFI SYSTEM ELIMINATES LED FLICKERING.

**SIMPLY
MATCH THE
ECO GEM SFI
DOWNLIGHT
WITH THIS
SDD400SFI
DIMMER.**



**DIM with
FLICKER
CONTROL**

For related
products
please
scan me

