



CANOPY SHP205 - 75/150W

IP66 LED recessed or surface mount canopy luminaire

Application

Commerical or industrial canopy applications

Design Specifications

- Stylish die-cast aluminium body
- Durable white powder coated finish
- High efficiency SMD LED chips, Clear tempered glass diffuser, 120 degree beam
- Built-in constant current non-dimmable LED driver, Symmetrical light distribution, 300 mm 3 core rubber flex
- Suits most traditional Canopy size (SHP205 RC)
- Dimensions (LWH mm) - SHP205/XXRCS 420 X 502 X 60 (7.5Kg). SHP205/XXSM 420 X 420 X 66 (7.5Kg)



Technical Specification


Model No.	Description	Input (ac) (V)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)
SHP205/75RC	LED CANOPY 75W LRG REC. 5K WH	240	75	9750	5000	120
SHP205/75RCS	LED CANOPY 75W SML REC. 5K WH	240	75	9750	5000	120
SHP205/75SM	LED CANOPY 75W SURFACE 5K WH	240	75	9750	5000	120
SHP205/110RC	LED CANOPY 110W LRG REC. 5K WH	240	110	14300	5000	120
SHP205/110RCS	LED CANOPY 110W SML REC. 5K WH	240	110	14300	5000	120
SHP205/110SM	LED CANOPY 110W SURFACE 5K WH	240	110	14300	5000	120
SHP205/150RC	LED CANOPY 150W LRG REC. 5K WH	240	150	19500	5000	120
SHP205/150RCS	LED CANOPY 150W SML REC. 5K WH	240	150	19500	5000	120
SHP205/150SM	LED CANOPY 150W SURFACE 5K WH	240	150	19500	5000	120




Model No.	CRI	Body Colour
SHP205/75RC	75	WHITE
SHP205/75RCS	75	WHITE
SHP205/75SM	75	WHITE
SHP205/110RC	75	WHITE
SHP205/110RCS	75	WHITE
SHP205/110SM	75	WHITE
SHP205/150RC	75	WHITE
SHP205/150RCS	75	WHITE
SHP205/150SM	75	WHITE

Photometric Data


SHP205 - 75



SHP205 - 150



SHP 205 - 110



Product Images

