

SLIMLINE SEAMLESS TC LINKABLE SL9706 - 4/22W

TC SEAMLESS SLIMLINE

Application

Great for commercial shop spaces

Design Specifications

- Selectable colour temperature 3000, 4000, 5000K, beam distribution 105 degree, CRI > 80
- Polycarbonate body profile and opal diffuser
- Integral constant current non-dimmable driver
- Plug and play flex and plug included
- Maximum connections: 280TC 55, 540TC 25, 840TC 17, 1140TC 12, 1440TC 10 UNITS
- Accessories: SL9706/32CM LINK (L 320mm)
SL9706/76CM LINK (L 760 mm)




Technical Specification

Model No.	Description	Input (ac) (V)	Power (W)	Lumens (lm)	CCT (K)	CRI
SL9706/280TC	LED LINKABLE 4W 280mm TC	240	4	300/380/300	3000/4000/5000	80
SL9706/540TC	LED LINKABLE 9W 540mm TC	240	9	750/800/750	3000/4000/5000	80
SL9706/840TC	LED LINKABLE 13W 840mm TC	240	13	1050/1200/1050	3000/4000/5000	80
SL9706/1140TC	LED LINKABLE 18W 1140mm TC	240	18	1550/1600/1600	3000/4000/5000	80
SL9706/1440TC	LED LINKABLE 22W 1440mmTC	240	22	1800/2000/1800	3000/4000/5000	80


Model No.	Body Colour
SL9706/280TC	WHITE
SL9706/540TC	WHITE
SL9706/840TC	WHITE
SL9706/1140TC	WHITE
SL9706/1440TC	WHITE

Dimensions

SL9706/280TC



SL9706/540TC



SL9706/840TC

