

TUBELINE BARE STB

Conventional LED bare battens 9-36 watt

Application

Conventional designed LED surface mount battens, ideal for most commercial interior service spaces

Design Specifications

- Pressed steel base with PVC body dimensions LWH: (9W) 625 x 55 x 77mm, (18W) 1225 x 55 x 77mm, (2x9W) 625 x 100 x 77mm, (2x18W) 1225 x 100 x 77mm
- Large terminal block, easy installation, 9, 18, 2 x 9, 2 x 18 watt models
- Quality white powder coat finish
- High efficiency LED T8 tubes fitted, CRI > 80, CCT 4000, 5000, 6000K
- Safety fuse installed, with emergency models compliant to AS/NZS2293 available
- Optional sensor models available



Performance

In Built Sensor - **OPTIONAL**

Sensor Type - **MICRO**

Technical Specification

Model No.	Description	Input (ac) (V)	Power (W)	Lumens (lm)	CCT (K)	CRI
STB/106 CW	LED BATTEN 9W 600mm 4K	240	9	800	4000	80
STB/112 CW	LED BATTEN 18W 1200mm 4K	240	18	1600	4000	80
STB/112 DL	LED BATTEN 18W 1200mm 5K	240	18	1700	5000	80
STB/206 CW	LED BATTEN 2 X 9W 600mm 4K	240	18	1700	4000	80
STB/206EM2500	LED EMERG. BATTEN 2 X 9W 4K	240	18	1700	4000	80
STB/212 CW	LED BATTEN 2 X 18W 1200mm 4K	240	36	3200	4000	80
STB/212 DL	LED BATTEN 2 X 18W 1200mm 6K	240	36	3400	6000	80
STB/212EM2500	LED EMERG. BATTEN 2 X 18W 4K	240	36	3200	4000	80

Model No.	Body Colour
STB/106 CW	WHITE
STB/112 CW	WHITE
STB/112 DL	WHITE
STB/206 CW	WHITE
STB/206EM2500	WHITE
STB/212 CW	WHITE
STB/212 DL	WHITE
STB/212EM2500	WHITE

Product Images

