





### **UNIFIT S9009TC2 - 10W**

Centre tilt 23 degree dimmable 10 watt LED downlight, with selectable CCT

# **Application**

Ideal for any residential or commercial interior space

## **Design Specifications**

- Die cast aluminium body profile
- Stylish white or black powder coat finish
- High output COB LED optics
- Multi-faceted reflector system, 60 degree beam distribution.
- Polycarbonate optical lens, CRI>80
- Remote constant current trailing edge dimmable LED driver with flex and plug

### **Performance**

- Dimmable YES
- Dimmer Type Trailing edge, optional 1-10V, DALI /





















# **Technical Specification**

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	сст (к)	Beam Angle (°)
	S9009TC2WH	240	10	750/900/850	3000/4000/5700	60
	S9009TC2BK	240	10	750/900/850	3000/4000/5700	60


Dimmable	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)
YES	80	MATT WHITE	76	82	80(H)
YES	80	MATT BLACK	76	82	80(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".





# **Dimensions**





# THE SFI SYSTEM ELIMINATES LED FLICKERING.

SIMPLY MATCH THE ECOGEM SFI DOWNLIGHT WITH THIS SDD400SFI DIMMER







DIM with FLICKER CONTROL

For related products please scan me



NSW/ACT: 02 9723 3099 QLD: 07 3879 5999 VIC/TAS/SA/NT: 03 9532 3168 WA: 08 9248 7458

