

SOLAR-400-TRIO Ceiling Light



Description

The SOLAR-RND range of surface mounted LED ceiling lights feature a simple, round and unobtrusive design while providing a 120° beam of uniform light-output through the use of high intensity SMDs (Surface Mounted Diodes).

The SOLAR-RND is constructed from polycarbonate and rated at IP54, making it ideal for usage in damp locations and in dwellings located close to coastal areas.

SOLAR-RND LED ceiling lights are available now with TRIO, the added option of changing the colour temperature output of the downlight with a dip switch at the back of the fitting. All models come complete with driver, (fully dimmable with suitable dimmers) have a lifetime of 40,000 hours and are backed by our Three Year Replacement Warranty.




Specification Features

Input Voltage:	AC 240V
Power (W):	35W
IP rating (IP):	IP54
Lumens (lm):	Warm White 3000K - 3150lm Neutral White 4000K - 3200lm White 5700K - 3250lm
LED type:	SMD
CCT:	3000K - 4000K -5700K (Switchable)
CRI:	≥80
Beam angle (°):	120°
Dimmable:	Yes**
Lifespan (hrs):	40,000hrs

** Tested on the Domus Dimmer Series. May work on others but not tested.

Diagrams / Additional



Item No.	Variant	Colour
SOLAR-RND-400-TRIO	20942	White
	20943	Black