Last modification

2023-06-28

Telbıx.

ORAS 12.420-BK3C 9329501052754



M DEFENSE HERSTINKT

The ORAS LED Wall Light - Black or Chrome has the capability of changing it's LED colour, between 3000k, 4000k and 5000k via an internal switch. This vanity light is ideal for diverse locations and environments with its IP44 rating

Overview

Family name	Oras
Categories	Wall Lights
Mounting	Surface
Usage	Indoor Lighting, Trade Selection

Color / Material

Black, Opal
Stainless Steel, Polycarbonate
Opal
Polycarbonate

42.0 4.0 6.0 41.5 2.5 3.0

<u>Size</u>

Fixture Length (cm)
Fixture Height (cm)
Fixture Projection (cm)
Canopy Length (cm)
Canopy Projection (cm)
Canopy Width (cm)

Specification

Voltage Input	240V
Total Wattage (max)	12
Globe Type	LED integrated SMD
Globe / Light Source qty	1
Globe / Light Source included	Yes
Lumens	850
Color Temperature	Warm White; Natural White; Cool White
Color Rendering	>84

Telbix.


Dimmable	No
Power Factor	>0.90
Control Gear Included	Yes-integrated
Current Output	280
Electrical Protection	CLASS I - HIGH VOLTAGE, EARTH REQUIRED
IP rating	IP44
Approvals	RCM
Assembly Required	Yes
Box Contents	Basic mounting screws, Instruction
Installation Required	Yes (by Licensed Electrician only)
Care Instructions	Do not use strong liquid cleaners, Wipe clean with a dry cloth
Replacement Warranty	*3 Years
Barcode	

GTIN

9329501052754

Image -dimensions

ORAS 12.420



Note: Dimensions are only a guide and may vary due to manufacturing variations.





Last modification

2023-06-28

Telbıx.

ORAS 12.420-CH3C 9329501052761



MACHINE AND

The ORAS LED Wall Light - Black or Chrome has the capability of changing it's LED colour, between 3000k, 4000k and 5000k via an internal switch. This vanity light is ideal for diverse locations and environments with its IP44 rating

Overview

Family name	Oras
Categories	Wall Lights
Mounting	Surface
Usage	Indoor Lighting, Trade Selection

Color / Material

Opal
Steel, Polycarbonate
onate

42.0 4.0 6.0 41.5 2.5 3.0

<u>Size</u>

Fixture Length (cm)
Fixture Height (cm)
Fixture Projection (cm)
Canopy Length (cm)
Canopy Projection (cm)
Canopy Width (cm)

Specification

Voltage Input	240V
Total Wattage (max)	12
Globe Type	LED integrated SMD
Globe / Light Source qty	1
Globe / Light Source included	Yes
Lumens	850
Color Temperature	Warm White; Natural White; Cool White
Color Rendering	>84

Telbıx.


Dimmable	No
Power Factor	>0.90
Control Gear Included	Yes-integrated
Current Output	280
Electrical Protection	CLASS I - HIGH VOLTAGE, EARTH REQUIRED
IP rating	IP44
Approvals	RCM
Assembly Required	Yes
Box Contents	Basic mounting screws, Instruction
Installation Required	Yes (by Licensed Electrician only)
Care Instructions	Do not use strong liquid cleaners, Wipe clean with a dry cloth
Replacement Warranty	*3 Years
Barcode	

GTIN

9329501052761

Image -dimensions

ORAS 12.420



Note: Dimensions are only a guide and may vary due to manufacturing variations.



