



HALO SO3000 - 18/35W

Dimmable architectural LED ceiling luminaire

Application

A creative design for residential or commercial spaces

Design Specifications

- Slim disc like appearance, 18 or 35 watt models
- Durable polycarbonate body profile with opal acrylic diffuser
- Simple twist lock installation mechanism
- High efficiency SMD LED chips, CCT 4000K standard, optional 3000K
- Integral constant current trailing edge dimmable LED driver
- Trim standard black

Performance

- Dimmable - **YES**
- Dimmer Type - **Trailing edge**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	SO3000/30CW	240	18	1450	4000	80
	SO3000/40CW	240	35	3300	4000	80

Dimmable	Dim (mm)	Diameter (mm)	Body Colour
YES	300(W) x 51(H)	300	BLACK
YES	400(W) x 68(H)	400	BLACK


Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".




Photometric Data

Unit: cd C0/C180 — C30/C210 —
cd C60/C240 — C90/C270 —

SO3000/30CW at 4000K



SO3000/40CW at 4000K





PIXIE AMBIENCE, CHANGE YOUR COLOUR TO MATCH YOUR STYLE.

The innovative PIXIE AMBIENCE SWITCH PLATES have been designed with the end user and installer in mind, allowing you to change the colour face plate as fashion demands.

For more
information
please
scan me

