



## LEEMAN MINI S9319 - 1.5W

LED 1.5 watt recessed MINI square profile wall luminaire

### Application

Residential stairs, walkways and commercial features

### Design Specifications

- Durable aluminium body profile
- Quality white powder coat finish or anodised silver
- High efficiency SMD LED chips, CCT 3000K, beam distribution 86 degree
- Frosted glass diffuser
- Suitable drivers - PLUTO EGL12V/6W, PLUTO 15DV, 30DV, 50DV
- 12V AC or DC non-dimmable driver required




### Technical Specification

Model No.	Input Voltage (V/AC)	Input Voltage (V/DC)	Power (W)	Lumens (lm)	CCT (K)	CRI
S9319 AS	12	12	1.5	70	3000	80
S9319 MW	12	12	1.5	70	3000	80

Model No.	Beam Angle (°)	Dimmable	Dim (mm)	Body Colour
S9319 AS	86	NO	60(L) x 60(W) x 30(H)	Anodised Silver
S9319 MW	86	NO	60(L) x 60(W) x 30(H)	White

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".


### Dimensions





## Photometric Data

Unit: cd C0/C180 — C90/C270 —





# PIXIE AMBIENCE, CHANGE YOUR COLOUR TO MATCH YOUR STYLE.

The innovative PIXIE AMBIENCE SWITCH PLATES have been designed with the end user and installer in mind, allowing you to change the colour face plate as fashion demands.

For more  
information  
please  
scan me

